

| | Standard | Result |
|---------------------------------|---|--|
| Thickness | ASTM F386 | 4.5 mm |
| Size | ASTM F2421 | 47.69" x 6.69" |
| Locking system ¹ | | 2G™ angling installation system |
| Wear layer | ASTM F410 | 12 mil (0.30 mm) |
| Surface treatment | | PU coating |
| Warranty ² | Commercial Residential | 10 Years Lifetime |
| Beveled Edge | | No |
| Standards | ASTM F3261 | Pass: Resilient flooring with Rigid Polymeric Core |
| Reaction to fire | ASTM E648-06 | Class 1 |
| Smoke density | ASTM E662-06 | Pass (< 450) |
| Flammability | ASTM D2859 | Pass |
| Slip resistance ³ | ASTM D2047 | Pass (Dry 0.8) |
| Staining resistance | ASTM F925 | Pass |
| Heat fastness | ASTM F1514 | Pass |
| Light fastness | ASTM F1515 | Pass |
| Abrasion resistance | ASTM D4060 | Pass (25,000 Cycles) |
| Dimensional stability | ISO 23999 | Pass |
| Acoustic impact noise reduction | ASTM E2179-09 ASTM E492-09 | ΔIIC = 25 dB IIC = 68 dB (6" Concrete Slab w/Drop Ceiling) IIC = 70 dB (6" Concrete Slab w/Drop Ceiling + QuietChoice) |
| Static load | ASTM F970 | Pass (750 psi @ 0.005") |
| Indentation - residual | ASTM F1914 | Pass |
| Thickness swell | NALFA 3.2 | Class 4 Heavy Commercial 1.11% |
| Adhesive | | None required; please install according to our installation instructions. |
| Environmental | FloorScore® SCS-EC10.3-2014 v4.0 ASSURE CERTIFIED™ NSF / ANSI 332 ISO 14001 / ISO 9001 | Indoor air quality certified; Compliant low emitting VOC emissions. Conformance with Rigid Core Flooring Standard SCS-0011 V1-0 Sustainability Assessment for Resilient Floor Coverings; Silver certified product Manufactured to quality and environment management systems standards |
| Recycling | | Suitable |
| Phthalate free | | Yes |

¹ 2G™ is a patented technology invented by Välinge Innovation AB. The 2G™ word mark and logo are registered trademarks owned by Välinge Innovation AB and any use of such marks is under license.

² Subject to terms. Commercial warranty covers light commercial use only

³ Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors including but not limited to: product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

Call: 888-266-4343

Email: info@karndean.com

Visit: www.karndean.com

| | Product Code | Size | | Box Quantity | |
|--------------|--------------|----------------|----------------|-----------------|-----------|
| | | inches | mm | ft ² | Pieces |
| Wood Designs | PVP120-SCB | 47.69" x 6.69" | 1211.2 x 169.8 | 26.56 | 12 Planks |
| | PVP121-SCB | 47.69" x 6.69" | 1211.2 x 169.8 | 26.56 | 12 Planks |
| | PVP123-SCB | 47.69" x 6.69" | 1211.2 x 169.8 | 26.56 | 12 Planks |
| | PVP128-SCB | 47.69" x 6.69" | 1211.2 x 169.8 | 26.56 | 12 Planks |
| | PVP142-SCB | 47.69" x 6.69" | 1211.2 x 169.8 | 26.56 | 12 Planks |
| | PVP145-SCB | 47.69" x 6.69" | 1211.2 x 169.8 | 26.56 | 12 Planks |
| | PVP147-SCB | 47.69" x 6.69" | 1211.2 x 169.8 | 26.56 | 12 Planks |
| | PVP148-SCB | 47.69" x 6.69" | 1211.2 x 169.8 | 26.56 | 12 Planks |
| | PVP150-SCB | 47.69" x 6.69" | 1211.2 x 169.8 | 26.56 | 12 Planks |
| | PVP151-SCB | 47.69" x 6.69" | 1211.2 x 169.8 | 26.56 | 12 Planks |